

DATASHEET



Portable EV Box

Secure and Safe


Type A+DC 6mA leakage protection
Over temperature protection
High protection grade up to IP65

Friendly Interface

OLED Display
Current can 8A, 10A, 13A, 16A, 20A, 32A, adjustable

High compatibility

Fully compatible with all ev in the market



SAE1772 Type 1



Schuko Plug




NEMA6-20P Plug



NEMA Plug



Blue CEE



IEC62196-2(Type2)



Model	ZECO035K-P035	ZECO7K-P7
Technical features		
Charging capacity	Up to 3.5KW	Up to 7KW
Input/Output power	230VAC±20%, 50/60Hz, 8A-10A-13A-16A adjustable, 1-phase	230VAC±20%, 50/60Hz, 8A-16A-20A-32A adjustable, 1-phase
RCD	30Ma RCD Type A and DC 6Ma RCD function	
Standby power	<2W	
Measuring accuracy	1%	
User interface	LED , OLED , Select button	
Certificate/Compliance	CE/IEC61851-1,IEC61851-22,SAEJ1772	
Charging Interface	5M cable, Type2 Plug	
Power Cord Plug	Schuko/NEMA6-20P	NEMA14-50/Blue CEE
Physical properties		
Protection	IP65,IK10,	
Special Protection	Temperature sensor and plug a dapter	
Cooling	Natural cooling	
Operating temperature	-30°Cto+55°C	
Humidity	Max.95%(non-regulating)	
Product Dimensions	210*88*50(L*W*H)mm	
Package Dimension	350*320*60(L*W*H)mm	
Net Weight	2.02Kg	2.5Kg
Gross Weight	2.25Kg	2.7Kg

Project Cases



zeco nex

One-stop EV Charging
Solution Provider



ZECONEX GROUP LIMITED

📍 Building A, Hankun Hi-tech Industrial Zone, Longteng Road,
Pingdi, Longgang District, Shenzhen, China

☎ + 86-755-84615006

✉ sales@zconex.com

🌐 www.zconex.com